

[54] **ELECTROPHORETIC IMAGING METHOD**

[75] Inventors: **John B. Wells**, Rochester; **Paul C. Swanton**, Webster; **John W. Weigl**, West Webster; **Edward Forest**, Rochester, all of N.Y.

[73] Assignee: **Xerox Corporation**, Stamford, Conn.

[22] Filed: **Sept. 20, 1972**

[21] Appl. No.: **290,618**

**Related U.S. Application Data**

[63] Continuation of Ser. No. 104,389, Jan. 6, 1971, abandoned.

[52] U.S. Cl. .... **96/1.3, 96/1 PE**

[51] Int. Cl. .... **G03g 13/22**

[58] Field of Search ..... **96/1 PE, 1 R, 1.3; 117/17.5**

**References Cited**

**UNITED STATES PATENTS**

2,758,525	8/1956	Moncrieff-Yeates .....	96/1.3
3,284,224	11/1966	Lehmann .....	117/17.5

3,384,565	5/1968	Tulagin et al. ....	96/1.3
3,689,399	9/1972	Isao Ota .....	96/1 PE
3,729,334	4/1973	Snelling .....	96/1 R

*Primary Examiner*—David Klein

*Assistant Examiner*—John L. Goodrow

*Attorney, Agent, or Firm*—James J. Ralabate; David C. Petre; Richard A. Tomlin

[57]

**ABSTRACT**

An electrophoretic imaging process wherein a suspension of particles in a carrier liquid are placed between a photoconductive electrode and a second electrode. With an electrical field applied between the photoconductive electrode and the second electrode the photoconductor is exposed to imagewise radiation which causes particles on the surface of the photoconductive electrode to be driven away in image configuration by charge exchange with the photoconductive electrode. The migrating particles form a negative image on the second electrode leaving a positive image behind on the photoconductive electrode.

**18 Claims, 10 Drawing Figures**